

LSC0507DEM

ELECTRIC SCISSOR LIFT

TOUGH WORLD. TOUGH EQUIPMENT.



Compliant with AU Standards

Security and Intelligence

- Intelligent control systems real-time monitoring of equipment status
- Sensors for weight and tilt to ensure personnel safety
- Intelligent charging system to extend battery service life

Easy to Control

- Drivable at full height
- Proportionate ascent and descent functionality
- Forklift pocket

Maintenance Friendly

- Self-lubricating pins
- Swing-out tray on both sides for easy maintenance
- Clear indication to facilitate troubleshooting
- Maintenance free batteries

Standard Features

- Forklift pockets
- Side anti-collision bars
- Extension platform
- Active pothole protection
- Motion alarm
- Emergency lowering system
- AC Drive motors
- Charging protection system
- Emergency battery disconnect
- Proportional controls
- Fault detection system
- Intuitive programming
- Folding guardrails
- Platform overload system

Specific Model Features

- 240kg platform capacity
- 6.5 meter working height
- Drivable at full height indoors
- 6.5 meter drive height outdoors



Access Service Australia Pty Ltd
ABN: 65 095 002 074

1300 272 111
Sales@accessservice.com.au

Access Service New Zealand Ltd
NZBN: 9429 0464 52139

0800 272 112
<https://accessservice.com.au>

We reserve the right to change the plan and parameters without informing the users as Liugong products are constantly updated and improved.

The product configuration and appearance in the photo are different from the actual model which should be subject to the actual product.

Liugong series logo in this brochure is a registered trademark of Guangxi Liugong Group Company, which has been legally authorized to use by us. Others are not allowed to use it without authorization.



Specifications

| Item | Unit | LSC0507DEM |
|---|------|-------------|
| Size | | |
| A - Max.Work Height | m | 6.5 |
| B - Max.Platform Height | m | 4.5 |
| C - Min.Platform Height | m | 0.94 |
| D - Platform Length | m | 1.3 |
| E - Platform Width | m | 0.72 |
| F - Max.Platform Extension Length | m | 0.6 |
| G - Overall Length | m | 1.47 |
| H - Overall Length (Without Ladder) | m | 1.31 |
| I - Overall Width | m | 0.76 |
| J - Overall Height (Rails Up) | m | 2 |
| K - Overall Height (Rails Down) | m | 1.64 |
| L - Wheelbase | m | 1.07 |
| M - Ground Clearance (Stowed) | mm | 60 |
| N - Ground Clearance (Raised) | mm | 16 |
| Performance | | |
| Rated Load on Working Platform | kg | 240 |
| Safe Working Load on Extended Platform | kg | 110 |
| Platform Occupants Max. (in/out) | / | 2 / 0 |
| Travel Speed (Stowed) | km/h | 4 |
| Travel Speed (Raised) | km/h | 0.7 |
| Turning Radius (Inside) | m | 0 |
| Turning Radius (Outside) | m | 1.5 |
| Up / Down Time | s | 23 / 21 |
| Max.Gradeability | / | 25% |
| Max. Working Slope (Lateral / Vertical) | ° | X1.5° / Y3° |
| Tire size | mm | 230 x 80 |
| Power | | |
| Drive Motor | kW | 0.45 DC |
| Battery | / | 100 Ah |
| Charger | / | 24 V 15 A |
| Weight | | |
| Total Weight | kg | 895 |

