

Engine Kubota D1703
Rated Power 25.7 kW (35 hp / 35 ps) @2,800 rpm
Nominal Amplitude Range 0.45 mm
Vibration Frequency Range 55 / 65 Hz
Centrifugal Force Range 35 / 40 kN
Working Width 1,200 mm
Operating Weight 2,700 kg

## 6027F ROLLER

## 6027F **SPECIFICATIONS** >>>

ENGINE	
Emission Regulation	Tier 3
Manufacturer	Kubota
Model	D1703
Rated Power	25.7 kW ( 35 hp / 35 ps) @2,800 rpm
Peak Torque	113 N·m
Number of Cylinders	3
Aspiration	Turbo
Cooling Type	Water
Displacement	1.647 L

12 V / 60 A
12 V / 72 Ah


DRIVE TRAIN	
Theoretical Gradeability	30%
Operating Speed, Fwd	0-10 km/h
Min. Outside Turning Radius	2,760 mm


PERFORMANCE	
Front Drum Static Linear Load	11.2 N/cm
Rear Drum Static Linear Load	11.2 N/cm
Number of Vibrating Drums	2
Nominal Amplitude	0.45 mm
Vibration Frequency	55/65 Hz
Centrifugal Force	35/40 kN
Drum Diameter	720 mm
Drum Width	1,200 mm
Drum Thickness	11 mm

2,700 kg
1,350 kg
1,350 kg

SERVICE CAPACITIES	
Fuel Tank	45 L
Engine Oil	7 L
Hydraulic Oil Tank	43 L
Cooling System	3 L
Vibrating Housing	5.5×1 L
Water Tank	180 L

DIMENSIONS	
A Overall Length	2,535 mm
B Overall Width	1,300 mm
C Compaction Width	1,200 mm
D Wheelbase	1,760 mm
E Steering Angle	±32°
G Min. Ground Clearance	255 mm
H Overall Height	2,860 mm
Swing Angle	7±1°





TOUGH WORLD. TOUGH EQUIPMENT.

## Guangxi LiuGong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China T: +86 772 388 6124 E: overseas@liugong.com www.liugong.com

Like and follow us:







## LG-6027F-TIER 3-102024-ENG

The LiuGong series of logos herein, including but not limited to word marks, device marks, letter of alphabet marks and combination marks, as the registered trademarks of Guangxi LiuGong Group Co., Ltd. are used by Guangxi LiuGong Machinery Co., Ltd. with legal permission, and shall not be used without permission. Specifications and designs are subject to change without notice. Illustrations and pictures may include optional equipment and may not include all standard equipment. Equipment and options varies by regional availability.